



## OIL&AIR VALUE

**FORK (Damper : Torco Lite RFF 7.5wt, Lower leg/Air Spring : XF Pure Slick Fluid)**

Model		Damper Oil(c.c)	Air Spring Oil(c.c)	Lower leg Oil(c.c)
RC32	RC	Closed cartridge	10	<b>Don't put oil</b>
MIG	RC	Closed cartridge		<b>Don't put oil</b>
SLIDE(32)	RL	140		15/per leg
X32	R	125		
VELVET	2 Pieces RL	140		15/per leg
	1 PiecesRL	70		15/per leg
SLANT SWEEP	RC	Closed cartridge		<b>Don't put oil</b>
	HLR	bleed		15/per leg
TRACE34 McQueen SLIDE Boost	RL/R	70		15/per leg
VENGEANCE	HLR/RC	85		20/per leg
	R	fill		
METRIC RV-1	Twin tube HLR/RC	100		
	Roughcut HLR	bleed		
	R	Damper oil:fill IFP Depth:110mm air presure:50psi		
TRACE36	RC	Closed cartridge		
	HLR	bleed	20/per leg	
REVEL-X	RC HLR	bleed	30(fill from left crown)	

**SHOCK (use Torco Medium RSF 10wt)**

Model	Damper Oil(c.c)	Air sleeve Oil(c.c)
Microlite series	fill	5
O2 series		
Stage series		
Vector Air series		

**HILO(use Mobil Multipurpose ATF Oil 7.5wt)**

Diameter(OD)	Traval(mm)	Oil(c.c)	Air(psi)
27.2	100	65	28
30.9	100	70	18
31.6	100	70	18
30.9	125	78	18
31.6	125	78	18

**HILO SL(use Mobil Multipurpose ATF Oil 7.5wt)**

Diameter(OD)	Traval(mm)	Oil(c.c)	Air(psi)
30.9	125	90	14
31.6			

**HILO SLS(use Torco Lite RFF 7.5wt)**

Diameter(OD)	Traval(mm)	Oil(c.c)	Air(psi)	IFP Deepth(mm)
30.9	125	fill	35	15
31.6	150			